

# RD4, RD5, RD6

## REMOTE WEIGHING DISPLAYS



### General Features

- 13.5mm – 100mm bright LED display.
- Displays weight and status
- RS-232C and R S485 data ports standard.
- Automatic communications sensing.
- Weather/sun visor included with wall mount models.
- Mounting accessories included.



### ...Azure Signature Series!

The RD4, RD5 and RD6 are high quality remote displays for industry in a durable housings.

The displays connect to the PT Azure Signature series weighing indicators and transmitters with continuous output and offer clear display of weight at extended viewing distances where the operator cannot be near the weight controller.

The RD5 and RD6 have industrial type robust stainless steel housings designed especially for outdoor installations. A large ( 57mm and 100mm respectively) bright high-efficiency LED display supported by an included sun visor provides excellent readability. Various serial data interfaces (RS-232C, RS-485 and 20mA CL) with automatic sensing are provided for transmission distances to 300 meters.



Accupoint weigh module

### Models Available

Model	RD4	RD5	RD6
<b>Mounting</b>	1/8 DIN Panel mount	Wall mount	Wall mount
<b>Display height</b>	13.5mm	57mm	100mm
<b>Display type</b>	Seven Segment bright LED	Seven Segment bright LED	Seven Segment bright LED
<b>Size [HxWxD] mm(inch)</b>	55x99x100 (2.16x3.90x3.94)	182x467x70 (7.2x18.4x2.8)	200x700x80 (7.9x27.6x3.2)
<b>Power Supply</b>	11-28VDC	220-240VAC	220-240VAC
<b>Input</b>	RS232C, RS-485. Auto-sensing	RS232C, RS-485, 20mA serial Current Loop. Auto-sensing	RS232C, RS-485, 20mA serial Current Loop. Auto-sensing
<b>Housing</b>	Aluminium with plastic front and stainless steel back.	Stainless Steel, IP65	Stainless Steel, IP65
<b>Environment</b>	-10C to +45C, IP65	-10C to +45C, IP65	-10C to +45C, IP65

Rev.180516